


INDUSTRIAL RTD ASSEMBLY

Resistance Temperature Detector

SERIES 466 SHEATHED RTD ASSEMBLY



Spring Loaded RTD Element
HOW TO ORDER



(1) Calibration & Configuration

	Code	Calibration	Configuration
	P21	"Single Element" 100 ohm	2 Wire
	P22	"Dual Element" 100 ohm	2 Wire
	P31	"Single Element" 100 ohm	3 Wire
	P32	"Dual Element" 100 ohm	3 Wire
	P41	"Single Element" 100 ohm	4 Wire
	P42	"Dual Element" 100 ohm	4 Wire
			Dual 3 Wire
			Single 4 Wire
			Dual 4 Wire

(2) Size & Sheath

Code	Dia.	Sheath Material
020	.125"	304 Stainless Steel
021		316 Stainless Steel
022		Inconel 600
030	.188"	304 Stainless Steel
031		316 Stainless Steel
032		Inconel 600
040	.250"	304 Stainless Steel
041		316 Stainless Steel
042		Inconel 600
050	.312"	304 Stainless Steel
051		316 Stainless Steel
052		Inconel 600
060	.375"	304 Stainless Steel
061		316 Stainless Steel
062		Inconel 600
080	.500"	304 Stainless Steel
081		316 Stainless Steel
082		Inconel 600

(4) Optional Bushing Sizes

Code	Thread # 2	Material
S66	3/8" NPT	Stainless Steel
B66	3/8" NPT	Brass
	1/2" NPT	Stainless Steel (standard)
B68	1/2" NPT	Brass
S812	3/4" NPT	Stainless Steel
B812	3/4" NPT	Brass
S816	1" NPT	Stainless Steel
B816	1" NPT	Brass

(4) Optional Accessories

Code	Accessory
A4	Aluminum Head
TR	Programmable Transmitter
PP4	Polypropolene Head
LA4	Light Duty Head
G3	Explosion Proof Head-1/2" Con.
G4	Explosion Proof Head-3/4" Con.

TEMTEX Temperature Systems, Inc

19053 W. US HWY 82, SHERMAN, TEXAS 75092

(800) 527-2009 - (903) 813-1500 - FAX (903) 813-1950

e-mail: temtex@temtex.net

WWW.TEMTEX.NET