


# THERMOCOUPLES PROBES

## SERIES 136 THERMOCOUPLE PROBE

Compacted Magnesium Oxide Insulation



### HOW TO ORDER

136 - (1) Calibration & Configuration - (2) Size & Sheath - (3) Length in Inches - (4) Options as required  
(Example- 14.5")

**(1) Calibration & Configuration**

Code	Calibration	Configuration
1TG	" T "	Grounded
1TU	Copper / Constantan	UnGrounded
1JG	" J "	Grounded
1JU	Iron / Constantan	UnGrounded
1KG	" K "	Grounded
1KU	Chromel / Alumel	UnGrounded
1EG	" E "	Grounded
1EU	Chromel / Constantan	UnGrounded
2TG	" T "	Grounded
2TU	Dual Element	UnGrounded
2JG	" J "	Grounded
2JU	Dual Element	UnGrounded
2KG	" K "	Grounded
2KU	Dual Element	UnGrounded
2EG	" E "	Grounded
2EU	Dual Element	UnGrounded

**(2) Size & Sheath**

Code	Dia.	Sheath Material
020	.125"	304 Stainless Steel
021		316 Stainless Steel
022		Inconel 600
030	.188"	304 Stainless Steel
031		316 Stainless Steel
032		Inconel 600
040	.250"	304 Stainless Steel
041		316 Stainless Steel
042		Inconel 600
050	.312"	304 Stainless Steel
051		316 Stainless Steel
052		Inconel 600

**(4) Optional Lead Wires (LW)**

Code	Lead Insulation Type
BL_*	Bare Leads ( Solid )
GG_*	Glass \ Glass Insulation
PP_*	PVC \ PVC Insulation
PAP_*	PVC \ PVC with Shield
SSO_*	S\S Overbraid over Glass
CCD	Coiled Cord ( 5 Ft. )

**(4) Optional Adjustable Fittings**

Code	Thread	Material
SA2	1/8" NPT	Stainless Steel
BA2	Max. .250" Dia.	Brass
SA4	1/4" NPT	Stainless Steel
BA4	Max. .375" Dia.	Brass
SA6	3/8" NPT	Stainless Steel
BA6		Brass
SA8	1/2" NPT	Stainless Steel
BA8		Brass

\* = Length in Inches (Example- BL3.5")